

ARINC 801

CONNECTORS AND TERMINI



Amphenol offers a multi-channel circular connector that complies with the ARINC specification. This connector, available in straight plug and wall mount receptacle, uses the ARINC 801 ceramic termini.

FEATURES & BENEFITS:

- Removable alignment sleeve insert for easy cleaning of fiber optic termini
- Three stages of alignment: shell-to-shell keys, guide pins, and ceramic alignment sleeves
- Includes all of the features of standard D38999 straight plug and wall mount receptacle shells:
 - Scoop-proof designs
 - Option for alternate keys and keyways
 - Rear accessory threads
 - Standard insertion/extraction tools (M81969/14-03)
- Genderless terminus allows for use on both sides of a connector
 - Precision ceramic ferrules and sleeves ensure accurate fiber to fiber alignment
 - Keyed to provide anti-rotation
 - Available with both PC and APC end-face finishes
 - Terminus body is crimped to the cable providing a "Pull-Proof" advantage

OPTIONS:

- Bulkhead Feed-Throughs
 - Panel mounted, double-ended jam nut receptacle with pin-pin contacts
- Hermetic
 - Customer specified optical sub-assemblies (fiber type, length, lead terminations) are installed into the connector and the back of the connector is sealed
 - Sealing rates in excess of 1×10^{-5} He/sec 40°C to $+85^{\circ}\text{C}$

Parameter	Performance
Insertion Loss (850 nm)	0.30 dB max., 0.15 dB typical (multi-mode)
Return Loss (850 nm)	-20 dB max., -40 dB typical (multi-mode)
Thermal Cycling	EIA 364-032D, Test condition VII (-55C to +100C; 5 cycles)
Altitude Immersion	TIA/EIA-455-15
Temperature Life	TIA/EIA-455-4 (100C for 1000 hours)
Vibration	TIA/EIA-455-11 (condition VI-G, eight hrs. per axis)
Mechanical Shock	TIA/EIA-455-14, Condition D
Humidity	TIA/EIA-455-5
Salt Spray	EIA-364-026B, Condition C (500 hours)
Fluid Immersion	Standard Aerospace Fluids

ARINC 801 CONNECTORS

Complete steps 1-8 to create your part number

1.	2.	3.	4.	5.	6.	7.	8.
Connector Type	Connector Series	Shell Finish	Shell Style	Shell Style - Insert Arrangement	Insert Material	Alternate Position	Interfacial Seal (Optional)
CF-	5A	4	6	11-02	P	N	2

1. Connector Type

CF-	Designates Multi-Channel Fiber Optic Connector
-----	--

2. Service Class

5A	Aluminum
6A	Composite
8A	Steel

3. Shell Finish

2	Black Anodized (Aluminum only)
4	Electroless nickel
6	Unplated Passivated (Steel only)
9	Olive drab cadmium
D	Durmalon™ (Nickel-PTFE) (Aluminum only)

2. Service Class

0	Wall mount receptacle ARINC 801
6	Straight plug ARINC 801
7	Jam Nut Receptacle ARINC 801

5. Select a Shell Size - Insert arrangement

See insert arrangements for ARINC 801 connectors below

6. Insert Material

AL	Aluminum
P	Plastic

7. Insert Type & Key/Keyway position

Insert Type and Keyway Position
Shell styles automatically determines termini gender.
Plug Connector = Socket termini
Receptacle Connector = Pin Termini
For keyway positioning, choose the alternate rotation suffix from the chart to the right.

8. Interfacial Seal


2	Interfacial Seal
---	------------------

An interfacial seal is NOT part of the ARINC 801 standard. The interfacial seal is offered by Amphenol High Speed Solutions and is NOT recognized by ARINC 801.

- Receptacles only
- If not desired, leave blank

INSERT ARRANGEMENTS

Front face of pin inserts illustrated




⊕ Contact Location ⊖ Jack Screw (Plug only) ● Guide Pin/Hole Location

ARINC 801 TERMINI

Ordering Information - ARINC 801 Termini

Amphenol ARINC 801 Termini Part Number	A Dia. Ref.	Ferrule Hole Tolerance
CF-198148-126	126	+1, -0
CF-198148-128	128	+2, -0

ARINC 801 TERMINI



Ordering Information - ARINC 801 Termini

ARINC 801 Equivalent	Radiall Equivalent	TE Connectivity Equivalent	Sabritec Equivalent	Amphenol Termini Part Number	Ferrule Type	Cable Type
LS	F725000419	1918614-1		CF-198148-126	PC for SM	1.6 - 2.2 mm loose structure
LM	F725003419	1828199-1		CF-198148-128	PC for 50/125 or 62.5/125 MM	1.6 - 2.2 mm loose structure
LSA	F725050419	1918616-1		TBD	SM APC	1.6 - 2.2 mm loose structure
TM	F725003519	1828200-1		TBD	PC for 50/125 or 62.5/125 MM	1.6 - 2.2 mm loose structure
TS	F725000519	-		TBD	PC for 200/230 MM	1.6 - 2.2 mm loose structure
TSA	F725050519	-		TBD	SM APC	1.6 - 2.2 mm loose structure
-	F725003118	-		TBD	PC for 50/125 or 62.5/125 MM	900 µm cable
-	F725003318	-		TBD	PC for 50/125 or 62.5/125 MM	1.2 mm tight structure

Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

AMPHENOL is a registered trademark of Amphenol Corporation. ©2015 Amphenol Corporation REV:3/18/2015